

# 东莞市国亚电子有限公司

DONGGUO GUOYA ELECTRONICS CO.,LTD

址:广东省东莞市长安镇增田村横增路 72号 地

Address: 72 Hengzeng Road, Zengtian Village, Chang' an Town, Dongguan cigy, Guangdong Province

E-mail: gya1688@gdgya.com

E-Tel: 0769-81769816 传真: 0769-87089563 网站: www.gdgya.com 诚信通: gya 旗舰店 QQ: 316563782

	61	0.01	
Type Document	Crimp Specification	<b>Revised /Edition</b>	A0
Date Issued:		Data Revised:	2019/06/09
Subject: 1515T-PSN			Issued By:
1.50mm Pitch Wire to E	Board Series Terminal.		Engineering Dept.

## **Description:**

Height and width of crimped core should he set as required.


(Crimped height and width of wire barrel)


According to the external diameter and the type of electric wire, the width of crimped sheath shall be adjusted

wire won't be easily taken off from contact nor too much crimped.

(Crimped width of insulation barrel)

## **Position Graph:**





#### Note:

- 1. Conductor crimp width. W1
- 2. Conductor crimp height. H2
- 3. Insulator crimp width. W1
- 4. Insulator crimp height. W2
- 5. Conductor wire shall be dimension long (mm) out A.
- 6. Naked part of sheathed wire must be located in the vicinity of center B.
- 7. The Crimp mouth must be equipped like Shell.



# 东莞市国亚电子有限公司

DONGGUO GUOYA ELECTRONICS CO.,LTD

地 址: 广东省东莞市长安镇增田村横增路 72号

Address: 72 Hengzeng Road, Zengtian Village, Chang' an Town, Dongguan cigy, Guangdong Province

E-Tel:	0769-81769816	传真:	0769-87089563	E-n
QQ:	316563782	诚信通:	gya 旗舰店	XX

nail: gya1688@gdgya.com 网站: www.gdgya.com

Type Document	Crimp Specification	<b>Revised /Edition</b>	A0
Date Issued:		Data Revised:	2019/06/09
Subject: 1515T-PSN			Issued By:
1.50mm Pitch Wire to B	Board Series Terminal.		Engineering Dept.

## **Requirement:**

	S	ubject:UL1007 or equ	uivalent type ele	ectric wire	
AWG#	Conductor (mm <sup>2</sup> )	Insulation Dia	ameter	Insulator skins length	Dim. L (mm) out
#24~#28	0.09~0.32mm <sup>2</sup> 1. 28~0. 70mm		1	1.3~1.8mm	0.6~0.8mm
Wire Gauge	Conductor Crimp Area		Insulator Crimp Area		Terminal Tensile
(AWG#)	Width(W1)	Height(H1)	Width(W2)	Height(H2)	Strength
#24		<b>0.60</b> –0. 65 <b>mm</b>		1.25-1.35mm	3.0Kgf
#26	0.90~1.00mm	<b>0.55-</b> 0. 60 <b>mm</b>	1.20mm Max	<b>1.15</b> –1.25 <b>mm</b>	2.0Kgf
#28	1	<b>0.50</b> -0. 55 <b>mm</b>	1	<b>1.10</b> –1. 20mm	1.0Kgf

### **Remarks:**

Unalike equipments and crimp reel molds skill facility or not shall be difference to result in dissimilar.

Signature: Lvtiansheng ENG Dongguan GuoYa Electronics CO.,LTD.