



Product Specification [产品规格书]:	ISSUED BY: Engineering Dept	
	Date Issued	2012/09/08
	Date Revised	2013/07/28

Subject [主题]:

2.50mm Pitch 8821 Series Connector Specification

This specification is referred to the 2.50mm series wire to board connector

索引【INDEX】

1. 适用范围【Scope】
2. 规格与料号【Spec and Part number】
3. 材质与表面处理【Disposal of Material and surface】
4. 额定等级【Ratings and applicable wires】
5. 性能【Performance】
 - 5-1. 电气的性能【Electrical Performance.】
 - 5-2. 机械的性能【Mechanical Performance】
 - 5-3. 环境性能及其它【Environmental Performance and Others】
6. 综合插入力及拔出力【Insertion/Withdrawal Force】
7. SMT 回流条件 SMT REFLOW CONDITION




Product Specification [产品规格书]:		ISSUED BY: Engineering Dept	
Subject [主题]: 2.50mm Pitch 8821 Series Connector Specification		Date Issued	2012/09/08
		Date Revised	2013/07/28
【1.适用范围 Scope】 此种规格包括 2.50mm Pitch 8821 Series 连接器规格说明. This Specification Covers the 2.50mm Pitch 8821 Series Connector Specification.			
【2.规格与料号 Spec and Part number】			
规格内容 Specification		产品料号 Production No.	产品图示 Picture of Product
端子/Terminal		8821T-XSN	NONE
胶壳/Housing		8821H-XX-XX	NONE
针座/Wafer		8821WVS-XXX-XXXX 8821WRS-XXX-XXXX	NONE
【3.材质与表面处理 Disposal of Material and surface】			
规格内容 Specification		材 质 Materials	表面处理 Disposal of Surface
端子/Terminal		磷铜/Phosphor Bronze 黄铜/ Brass	先冲后镀 锡 / Tin 70μ" min 、 镍/Ni: 30μ" min
胶壳/Housing		PA66	UL 94V-0
针座/Wafer	Base	PA66	UL 94V-0
	PIN	黄铜/Brass	Over Tin 70μ" Plated ; Over 30μ" Nickel
	Solder tab	黄铜/Brass	Over Tin 70μ" Plated ; Over 30μ" Nickel
(上述参数请以工程图为准 / Please Refer to the Project drawing for the above Specification)			
【4. 额定等级 Ratings and applicable wires】			
项 目【Item】		规 格【Standard】	
额定电压 Rated Voltage (Max.)		250V	[AC/DC]
额定电流 Rated Current (Max.)		3A	
使用温度范围 Ambient temperature Range		-25℃~+85℃	
适用线径 Applicable wire insulation O.D		AWG 22#~30# Insulation O.D. 1.90mm(Max.)	
【 *升温时含端子.Including terminal temperature rise. 】			
WRITTEN BY:Yangzhengguo		APPROVED BY:Lvtiansheng	Sheet: 2 of 8



Product Specification [产品规格书]:		ISSUED BY: Engineering Dept	
Subject [主题]: 2.50mm Pitch 8821 Series Connector Specification		Date Issued	2012/09/08
		Date Revised	2013/07/28

【5.性能 PERFORMANCE】




5-1. 电气的性能 Electrical Performance.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】
5-1-1	接触阻抗 Contact Resistance	公母配合,开放电压 20mV 以下,电流 10mA 检测连接器 A~B 区. Mate connectors, measure by dry circuit, 20mV MAX, 10mA. (Based upon EIA-364-06A). 	Initial: 10 milliohms Max. After Test: 20 milliohms Max.
5-1-2	绝缘阻抗 Insulation Resistance	公母配合,在相邻端子,端子与地片之间,使用 500V 的直流电,检测连接器. Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond.B)	1000 Megohms Min.
5-1-3	耐电压 Dielectric Strength	公母配合,在相邻端子,端子与地片之间,使用 1000V 的交流电 1 分钟,检测连接器. Mate connectors, apply 1000V AC for 1 minute between adjacent terminal or ground. (Based upon EIA-364-20A / MIL-STD-202 Method 301)	不出现中断等情况 No Breakdown and Flashover
5-1-4	铆线后端子接触阻抗 Contact resistance on crimped portion	铆线后之端子,开放电压 20mV 以下,电流 10mA 检测连接器. Crimp the applicable wire on to the terminal measure by dry circuit 20mV MAX, 10mA.	10 milliohms Max.




Product Specification [产品规格书]:		ISSUED BY: Engineering Dept	
Subject [主题]: 2.50mm Pitch 8821 Series Connector Specification		Date Issued	2012/09/08
		Date Revised	2013/07/28

5-2. 机械的性能 Mechanical Performance.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】
5-2-1	插拔力 Insertion & Withdraw Force	以每分钟 $25.4 \pm 3\text{mm}$ 的速率插入和拔出. Insert and withdraw Connectors at the speed rate of $25.4 \pm 3\text{mm/minute}$.	参照第 6 项 Refer to paragraph 6
			
5-2-2	端子保持力 Terminal/ Housing Retention Force	以每分 $25.4 \pm 3\text{mm}$ 的速率,将端子从 Housing 内轴向拔出的力量. Apply axial pull out force at the speed rate of $25.4 \pm 3\text{mm/minute}$ on the terminal assembled in the housing.	19.6N {2.0kgf} Min.
			
5-2-3	端子插入力 Terminal Insertion Force	铆线后之端子插入 Housing 所需最大力量. Insert the crimped terminal into the housing.	14.7N {1.5kgf} Max.
5-2-4	Pin 针保持力 Pin Retention Force	以每分 $25.4 \pm 3\text{mm}$ 的速率,将 PIN 针从 Wafer 内轴向拔出的力量. Apply axial push force at the speed rate of $25.4 \pm 3\text{mm/minute}$.	19.6N {2.0kgf} min.
			



Product Specification [产品规格书]:				ISSUED BY: Engineering Dept					
Subject [主题]: 2.50mm Pitch 8821 Series Connector Specification				Date Issued		2012/09/08			
				Date Revised		2013/07/28			
项 目 【Item】		条 件 【Test Condition】		规 格 【Requirement】					
5-2-5	端子压着强度 (Crimped connections)	固定铆线后的端子，使电线与端子分离时所需的最小力量。 Fix the crimped terminal, apply axial pull out force on the wire. (Do not crimp insulation part).		AWG#	#22	#24	#26	#28	#30
				Spec. .kgf. Min.	5.0	3.0	2.0	1.0	0.5
				Note> As for unspecified wire sizes in this specification define values with clients					
5-3. 环境性能及其它 Environmental Performance and Others.									
项 目 【Item】		条 件 【Test Condition】		规 格 【Requirement】					
5-3-1	重复插拔 Repeated Insertion/ Withdrawal	以每分锺不超过 10 次的速率,将公母插拔 50 次。 When mated up to 50 cycles repeatedly by the rate of 10 cycles per minute.		接触阻抗 Contact Resistance		20 milliohms Max.			
5-3-2	温升测试 Temperature Rise	公母对插后,在通过额定电流下,所测定的温度。 Carrying rated current load. (UL 1977)		温升测试 Temperature rise		30℃ Max.			
5-3-3	耐振动性 Vibration	振幅: 1.5mm P-P 时间: 10~55~10 HZ in 1 minute 持续时间: 每轴向 2 小时 Amplitude: 1.5mm P-P Sweep time: 10~55~10 HZ in 1 minute Duration: 2 hours in each X.Y.Z axials. (Based upon EIA-364-28B/MIL-STD-202 Method 213B Cond.A)		外观 Appearance		无异状 No Damage			
				接触阻抗 Contact Resistance		20 milliohms Max.			
				瞬断 Discontinuity		1 micro-second Max.			
5-3-4	耐冲击性 Shock	在 X.Y.Z 上 6 个方向上,以 490m/s ² (50g 的力量)冲击下各 3 回.490m/s ² {50G}, 3 strokes in each X.Y.Z. axes. (Based upon EIA-364-27B/MIL-STD-202 Method 213B Cond.A)		外观 Appearance		无异状 No Damage			
				接触阻抗 Contact Resistance		20 milliohms Max.			
				瞬断 Discontinuity		1 micro-second Max.			
WRITTEN BY:Yangzhengguo				APPROVED BY:Lvtiansheng				Sheet: 5 of 8	



地址: 广东省东莞市长安镇增田村横增路 72 号

Address: 72 Hengzeng Road,Zengtian Village,Chang' an Town,Dongguan city,Guangdong Province

E-Tel: 0769-81769816 传真: 0769-87089563

E-mail: gya1688@gdgya.com

QQ: 316563782

诚信通: gya 旗舰店

网站: www.gdgya.com

Product Specification [产品规格书]:			ISSUED BY: Engineering Dept	
Subject [主题]: 2.50mm Pitch 8821 Series Connector Specification			Date Issued	2012/09/08
			Date Revised	2013/07/28
项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】	
5-3-5	耐热性 Heat Resistance	85±2℃,96 hours. (Based upon MIL-STD-202 Method 108A Cond.A)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
5-3-6	耐寒性 Cold Resistance	-25±5℃,96 hours. (Based upon EIA-364-105)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
5-3-7	耐湿性 Humidity	温度: 40±2℃ 湿度: 90~95%(RH) 持续时间: 96 hours Temperature: 40±2℃ Relative Humidity: 90~95% Duration: 96 hours (Based upon EIA-364-31A/MIL-STD-202 Method 103B Cond.B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
			耐电压 Dielectric Strength	Must meet 5-1-3
			绝缘阻抗 Insulation Resistance	500 Megohms Min.
5-3-8	温度变化 Temperature Cycling	从-25℃持续 30 分锺升至+85℃持续 30 分锺,循环 5 次. 5 cycles of: a) -25℃ 30 minutes. b) +85℃ 30 minutes. (Based upon EIA-364-32B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
5-3-9	盐水喷雾 Salt Spray	在温度 35±2℃,盐水浓度 5±1%下,盐水喷雾 24±1 小时. 24±1 hours exposure to a salt spray from the 5±1% solution at 35±2℃. (Based upon EIA-364-26B/MIL-STD-202 Method 101D Cond.B). 此项测试适用于 8821T-XSN 先冲后镀产品	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
WRITTEN BY:Yangzhengguo			APPROVED BY:Lvtiansheng	
			Sheet: 6 of 8	



地址: 广东省东莞市长安镇增田村横增路 72 号

Address: 72 Hengzeng Road,Zengtian Village,Chang' an Town,Dongguan city,Guangdong Province

E-Tel: 0769-81769816 传真: 0769-87089563

E-mail: gya1688@gdgya.com

QQ: 316563782

诚信通: gya 旗舰店

网站: www.gdgya.com

Product Specification [产品规格书]:				ISSUED BY: Engineering Dept	
Subject [主题]: 2.50mm Pitch 8821 Series Connector Specification				Date Issued	2012/09/08
				Date Revised	2013/07/28

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】	
5-3-10	焊锡附着性 Solder-ability	焊接时间: 3±0.5 秒. 焊接温度: 245±5℃. Soldering Time: 3±0.5second. Solder Temperature: 245±5℃. (Based upon EIA-364-52)	Solder Wetting	浸渍面积需 95%以上 95% of immersed area must show no voids, pin holes.
5-3-11	焊锡耐热性 Solder-Resistance	焊接时间: 5~10 秒. 焊接温度: 255+5/-5℃. Soldering time:5~10 sec solder. Temperature:255+5/-5℃. (Based upon EIA-364-56A)	外观 Appearance	无异状 No Damage

【6.综合插入力及拔出力 INSERTION/WITHDRAWAL FORCE】 <Connector mating force>

PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	30 次拔出力(最小值) 30 th Withdrawal (kgf Min.)	PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	30 次拔出力(最小值) 30 th Withdrawal (kgf Min.)
Single	1.00	0.20	09	6.50	1.20
02	3.00	0.60	10	7.00	1.40
03	3.50	0.80	11	7.50	1.40
04	4.00	0.90	12	8.00	1.60
05	4.50	0.90	13	8.50	1.60
06	5.00	1.00	14	9.00	1.80
07	5.50	1.00	15	9.50	2.00
08	6.00	1.20	16	10.00	2.60

注: 以上插拔次数为 30 次 Note: Insertion and Withdrawal for 30Cycles

WRITTEN BY:Yangzhengguo	APPROVED BY:Lvtiansheng	Sheet: 7 of 8
-------------------------	-------------------------	---------------



Product Specification [产品规格书]:

ISSUED BY: Engineering Dept

Subject [主题]:

2.50mm Pitch 8821 Series Connector Specification


Date Issued

2012/09/08

Date Revised

2013/07/28

【7. SMT 红外线回流条件 SMT INFRARED REFLOW CONDITION】



温度条件曲线图/ 基板上温度

TEMPERATURE CONDITION GRAPH/ (TEMPERATURE ON BOARD PATTERN SIDE)

注记: 由于 P.C 板等焊接装置改变条件,所以请预先用自己的装置检查回流焊的条件.

Notes: Please check the reflow soldering condition by your own devices beforehand. Because the condition changes by the soldering devices, P.C. boards, and so on.